



Designed to Print on Everything
Introducing New U2 MobileS Ink Jet Printer

We Got You Covered



Coated Paper




Metal & Aluminum



Hard Plastic



Flexible Plastic



Construction Materials



U2 MobileS Specifications

Display	3.5" color LCD with LED backlight
User Interface	Simple and easy-to-use operating system
Input Device	Pocket-sized IR remote keypad
Available Languages	English, Chinese (Traditional), Chinese (Simplified), Japanese, Russian, Korean, German, Portuguese, Spanish, French, Italian, Turkish, Hungarian, Slovak, Czech, Swedish, Romanian, Serbian, Bulgarian, Polish
Print Engine	HP Thermal Ink Jet Technology
Print Resolution	Max 300*400 dpi
Print Distance	Max 1663.7 mm
Message High	Alphanumeric, logos, date/time, shift code, counter, lot box code
Print Capability	Up to 4 lines and 12.7mm (0.5") selectable front size from 2.7mm to 12.7mm
Barcodes	EAN8, EAN13, EAN14, EAN128, UPCA, UPCE, CODE39, CODE128, TF14 (SCC-14), NVE18 (SSCC-18), C25INTER, CODABAR, PDF417, DATAMATRIX, QR Code and 2D barcode
Data Interface	USB2.0*1, RS-485*1
Dimensions	143.5 (L) x 219 (W) x 143 (H) mm
Weight	1.13 kg (2.49 lbs)

Long Lasting Battery

Rated Capacity	1,840 mAh
Standard Voltage	11.1V
Input/Output Voltage	12.6V
Charging Voltage	12.6V
Charging Temperature Range	0°C - 45°C (32°F - 113°F)
Discharging Temperature Range	-20°C - 60°C (-4°F - 140°F)
Dimensions	100.3 (L) x 56.3 (W) x 21 (H) mm
Weight	150g (0.33 lbs)
Cycle Life	More than 300 cycles

Ink Solution

A wide range of ink selections for printing on porous, semi-porous and non-porous substrates

Environment

Operation Temperature Range	5°C - 40°C (41°F - 104°F)
Storage Temperature Range	-20°C - 70°C (-4°F - 158°F)



WWW.ANSER-U2.COM