



V5 Compact

Compact design / mono-block

High quality printing at a reduced cost







FEATURES

Native 180dpi resolution
Multiple densities and contrasts
High quality barcode printing. GS-1 standard
Intuitive user environment
On screen preview of printing layout (WYSIWYG)
Oil based and UV LED ink
Integrated Wi-Fi
External message selection through hardware

PROS

Personalisation. Short runs. Promotions Stock reduction of pre-printed boxes Practically zero maintenance No interruptions when adding consumables





limitronic.com

SPECIFICATIONS

PRINT

Printer head resolution: 180 dpi

Print speed:

30 m/min @ 180 dpi 0.2 - 96 m/min according to the resolution

Height: 72 mm

Maximum length: 1100 mm

Densities: 3 levels

Fonts:

True Type $^{\text{™}}$, Open Type $^{\text{™}}$ fonts

Character coding: Unicode

Barcodes:

GS-1 Standard

EAN/UPC, ITF-14, GS1-128, GS1 Datamatrix,

GS1 QR Code

Printing in various fields:

User (personalised fields) and automatic based fields (expiration dates, shift codes, counters)

Orientation:

Vertical (side of the product)

ELECTRICAL

Power supply:

Auto-range

88-264VAC / 47-63 Hz, 108 W (max)

Input:

2 x printer signals

1 x encoder

 $5 \times programmable$ electronics (external message selection)

Output

2 x programmable electronics

Communication ports:

- 1 x RS-232
- 1 x Ethernet 10/100
- 1 x USB
- 1 x WiFi

ENVIRONMENTS

Working environment:

5 - 40 °C (41 - 104 °F)

Protection:

IP 50

USER INTERFACE

Touch screen, colour, 7"
Message selection with preview
WYSIWYG
Diagnostics

COMMUNICATIONS

Individual communications protocol Windows™ Driver Remote assistance

OTHERS

Weight: 4,5 kg

Ink

Oil based ink UV LED ink



Colours:

Black

Black (high contrast)

Cyan Magenta

Yellow

Others (consult)

PRINTABLE PRODUCTS

Cardboard, glossy paper, art paper, paper, fabrics, wood, plastic, metal, nylon, EPS, and more.

OPTIONS

Encoder, alarm beacon, purge assist

v5 Compact

UV LED


UV LED




Printing immediately sets Useful, long life span with low maintenance Energy efficient

FEATURES


Several heights available Instant on/off Safety through double activation input Adjustable intensity





DIMENSIONS









V.L. Limitronic, S.L. Calle Andorra 19 Pol. Ind. Ciudad del Transporte II 12006 Castellón - Spain Tel. (+34) 964 562 199 Fax. (+34) 964 503 070 info@limitronic.com

limitronic.com